

SMX 77



Models: 2-24



Models: 3-36



Standard equipment:

- Reduction Ø 70 - Ø 50 mm



- Cloth filter



Optional:

- Color filter



- Oven kit Ø 40



Equipped with:

- 3 silenced two stage motor (SMX 3-36 model). • 2 silenced two stage motor (SMX 2-24 model).
- Suction system with by-pass cooling. • S/S tank. • Manual filter shaker.
- Professional closing hooks. • Static electric shock inhibitor. • Liquid float valve. • Cloth filter.
- Filters (optional) against thin dust or Hepa. • Though integrated accessory storage facility.
- Non-overturning steel structure. • Available with body and cover entirely made of S/S AISI 304. • Traceless wheels. • Accessories Ø 50.

	SMX77 2-24	SMX77 3-36
code	0.056.0002	0.056.0004
abs. power W	2000	3000
n° / type motor	2x two stages universal	3x two stages universal
column depression	23,6 kPa (2400 mmH2O)	23,6 kPa (2400 mmH2O)
suction air	108 l/s	162 l/s
tank volume/dust capacity/liquid capacity	77 l / 45 l / 50 l	77 l / 45 l / 50 l
noise level	74 dB(A)	76 dB(A)
voltage	230 V~50-60 Hz (1Ph)	230 V~50-60 Hz (1Ph)
filtering surface	4300 cm ²	4300 cm ²
filtering capacity	5 µm	5 µm
cable lenght	7,5 m	7,5 m
dimensions / weight	70x91x141cm/66Kg-145.2 lbs	70x91x141cm/67Kg-147.4 lbs