# MagiX 35 LSMG II

Electro-hydraulic mobile short-rise scissor lift, 3.5 t capacity





## Application

- ☐ Repair and maintenance
- □ Tyre change

# Description:

- □ Double hydraulic system with 2 cylinders under each scissor section, therefore no compressed air and no safety ratchet necessary
- $\hfill \Box$  Leverage of full capacity 3.5 t from the lowest position
- $\hfill\square$  Mechanic synchronization through cross-bars
- ☐ Emergency lowering valves can manually be opened
- ☐ Sturdy scissor construction for high directional stability
- ☐ Ramps and platforms made of tear plates, for easy drive-on, also with wet wheels
- $\hfill\square$  Base frames, platforms and ramps galvanized as standard
- ☐ Increased stability by roller guides under the platform
- Mobile-kit in standard scope of delivery, consisting of: rollers and lever for moving of the scissor lift
- ☐ Rubber blocks 1 set = 4 pcs, H=40 mm included in scope of delivery

#### Standard colours:

- □ Platforms & ramps: galvanized
- ☐ Scissors: RAL 7016 grey

## Versions:

☐ Available with different voltages

# Optional extras:

- ☐ Set of expansion bolts
- □ Set rubber blocks, 20, 40, 60, 70, 80 and 100 mm



Scan the QR-Code for detailed product information.

Further Information on www.autopstenhoj.com

### **AUTOPSTENHOJ GmbH**

Sandkampstraße 90 D-48432 Rheine

**\** +49 5971 8602-02

info@autopstenhoj.com

### **AUTOPSTENHOJ GmbH**

Barrit Langgade 188-190 DK-7150 Barrit

**4** +45 76 82 13 30

info@autopstenhoj.com

Technical data	
Lifting capacity	3,500 kg
Lifting height	895 mm
Working height	1,000 mm + Rubber pads
Lifting / lowering time	16 sec.
Pump unit	2.2 kW
Voltage	3Ph - 230/400V - 50 / 60 Hz

Scissor platforms	
Platform length	1,400 – 1,974 mm
Platform width	480 mm
Distance between platforms	1,000 mm
Min. height	105 mm
Depth of recess	0 mm















