

### LMX XP

**T.S.** Total Stop



#### Standard equipment:


- 3.700.0036 Gun M22 - 3/8.



- 3.701.0015 Lance M22 high/low pressure (mod. 1211 XP)



- 6.602.0026 Lance M22 high/low pressure with nozzle (mod. 2007 XP)



- 3.103.0050 Nozzle type 045 (mod. 1211 XP)



- 4.618.0053 High pressure hose 10 m



- Power cable 5 m

#### Equipped with:

- Three ceramic coated pistons, brass axial pump head with built-in by-pass valve.
- Total Stop. • Suction and delivery S. S. valves. • Detergent built-in tank for indirect suction. • Pressure regulator. • Glycerine pressure gauge. • Hose reel. • Accessory holder. • Ergonomic handle.

**VERSION**  
**60**  
**Hz**  
**AVAILABLE**  
**DETAILS PAGE 9**

	LMX 1211 XP	LMX 2007 XP
code	8.613.0001	8.613.0015
operat. pressure/max	120/150 bar-1740/2175 psi	200/220 bar-2900/3190 psi
delivery rate	660 l/h-2.91 GPM	420 l/h-1.85 GPM
abs. power/voltage	3300W - 230V~50Hz 1 ph	3300W - 230V~50Hz 1 ph
motorpump type/RPM	MPBX2/2800 RPM	MPBX2/2800 RPM
max. water inlet temperature	40 °C	40 °C
dimension/weight	59x37x87cm / 28 Kg - 61,6 lbs	59x37x87cm / 28 Kg - 61,6 lbs