

## Thermic 10 HW Hot water self-contained unit



**T.V.** Thermal Valve

### Equipped with:

- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- By-pass thermal protection with safety valve.
- Electrical start with full engine functions control.
- Auxiliary belt driven sturdy alternator.
- Lombardini diesel engine 15LD400 (air cooled).
- Pump-motor gearbox (1.650 RPM).
- Automatic engine RPM regulator.
- Integrated detergent suction with external suction probe.
- Electrical start with engine functions control.
- Unique diesel tank for engine and burner.
- Battery included.

### Standard equipment:

- 3.700.0043 Gun MV 975 3/8" M with quick connection



- 6.602.0044 Lance 900 mm with quick connection.



- 3.103.0052 Nozzle type 055



- 4.618.0012 High pressure hose 10 m



### Optional:

- 5.613.0252 S. S. header tank (high pressure chemical)
- 6.608.0014 Varnished soundproofing steel cover set code
- 6.608.0020 Trolley set with inflateable wheels & handles



### Thermic 10 HW

|                               |                               |
|-------------------------------|-------------------------------|
| code                          | 8.601.0099                    |
| operat. pressure              | 170 bar-2465 psi              |
| delivery rate                 | 1020 l/h-4.49 GPM             |
| engine type/hp                | Lombardini 15LD400/10         |
| pump type/RPM                 | CL5/1650 RPM                  |
| max. water inlet/outlet temp. | 40/140 °C                     |
| dimension/weight              | 68x99x74cm / 140 Kg - 208 lbs |