

4-ram lift 4.55 F480/550 (KA 1550/3000)

Electro-hydraulic 4-ram lift, 5.5 t, with platforms



Application

- Check-in
- Repairs and maintenance
- Wheel alignment
- Test

Approvals / recommendations

- QL 4.55 F 480:
BMW / Mini
- QL 4.55 F 550:
Renault,
Volkswagen Group
- Rolls-Royce

Description:

Steel cassette:

- Waterproof steel cassette

Hydraulic unit:

- 2 separate hydraulic units with hard-chrome plated cylinders
- Electronic synchronization between the hydraulic units and pre-programmed top stop
- Flexible synchronization and safety system
- Corrosion-free guiding elements
- Pump unit with immersed motor
- Hydraulic oil
- Pneumatic emergency lowering
- Programmable pushbutton control unit
- Air preparation unit for oil and regulated compressed air (min. 6 bar / max. 10 bar)

Superstructure:

- A set of platforms with drive-on ramps and stops
Platforms with tolerances of only max $\pm 0,5$ mm length- and crosswise
- With two recesses front and rear, as well as distance pieces covering the entire length and fixated by steel edges in sides
- Preparation for innovative air supply for jacking beam

Standard colours

- Platforms: RAL 7016 - grey
- Ramps: RAL 3020 - red
- All surfaces zinc-coated as standard

Versions:

Steel cassette:

- Zinc-coated
- Coated

Installation:

- Superstructure on floor
- Superstructure in floor
with or without floor alignment system

Contact us with regard to the possibilities of combining with other wheel alignment equipment!

Optional extras:

- LED-lighting set
- Precision slip plates
- Scissor jack

Special colours available on request!

