

NEW

MEGA 6200 BT



Standard equipment:



- 2 x 5.511.1845
PPL brush Ø 457 mm - 18"



- 4.508.1196
Front squeegee blade L.1027 mm
Shore 40 Th. 3 mm
- 4.508.1195
Rear squeegee blade L.1150 mm
Shore 33 Th. 4 mm



- Suitable for maintenance and deep cleaning of medium and large areas (up to 4.500 m²) with a considerable reduction of cleaning costs
- More than 60/80 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Antifoam device
- Self-levelling brushes
- High-performance batteries resulting in high-working efficiency.

	MEGA 6200 BT
code	8.575.0013
power supply	24V
scrubbing / squeegee width	900 / 1000 mm
max working capacity	6200 m ² /h
detergent tank capacity	140 l / 36.99 gal
recovery tank capacity	150-180 l / 39.6-47 gal
traction type / power	front motorwheel / 1000 W
RPM / pressure on the brushes	150/50 kg / 176 lbs
brush motor power	1250 W
max gradient empty/full tank	10% / 7%
depression / vacuum motor	1734 mmH ₂ O/550W
dimensions / weight	175x93x149 cm / 220 kg



Quick lock recovery tank cap allows for fast and easy cleaning and sanitization of the tank; the tilting tank together with a large size drain hose allow the complete emptying of the tank and the removal of any type of solid dirt. The antifoam device protects suction motor, as well as the electronic floating switch that stops suction when the tank is full.

Optional accessories:



- 0.107.0008
Battery box Pb-acid
24V 500Ah C5



- 0.108.0003
Battery Charger 24/36V
50/60A - 220-240/50-60



- 4.508.1251 Polyurethane front blade L.1027 TH. 3
- 4.508.1252 Polyurethane rear blade L.1150 TH. 4



- 5.511.1848
Tynex brush Ø 457 mm-18"
- 5.511.1849
PPL 0,03 brush Ø 457 mm-18"
- 5.511.1847
PES brush Ø 457 mm-18"



- 5.511.1850
EWU pad driver Ø 457 mm-18"



- 6.508.0150 - Ø 457 mm-18"-
beige (5 pcs.)
- 6.508.0151 - Ø 457 mm-18"-
green (5 pcs.)
- 6.508.0142 - Ø 457 mm-18"-
black (5 pcs.)

Comfortable steering wheel.
User friendly control panel, provided with hour meter, speed adjustment knob and detergent solution low level warning light.
All motors are protected by thermal breakers.



80 kg of continuous brush plate pressure with Self Leveling System to strongly and deeply removing any kind of dirt on any kind of floor.
Strong oil-proof polyurethane wheels.
500 Ah C5 battery box allowing continuous working time up to 5 hours.

Built with strong components, Mega 6200 have been designed to resist even to extreme stresses; the frame is made of steel profiles with a thickness varying from 5 to 12 mm, protected with a high resistance corrosion-proof paint.

