

# Application

- ☐ Check-in
- ☐ Repair and maintenance
- □ Testing equipment

#### **Approvals**

□ Volkswagen Group

# **Biglift 4.55 Combi**

Electro-hydraulic 2xtwin-ram lift, 5.5 t with platforms and Free-wheel device with arms

# Description:

#### Steel cassette:

☐ Waterproof steel cassette

## Hydraulic unit:

- ☐ Hard-chrome plated cylinder
- ☐ Flexible synchronization and safety system
- ☐ Corrosion-free guiding elements
- ☐ Pump unit with immersed motor
- ☐ Ecological hydraulic fluid
- ☐ Pneumatic emergency lowering
- Programmable pushbutton control unit great stability, even with uneven weight distribution (all 4 cylinders in operation)

#### Superstructure:

☐ A set of platforms with drive-on ramps and stops

#### Free-wheel device Saav:

- □ Double telescopic arms, crosswise adjustable
- ☐ Internal arm locking system
- Low minimum height

# Standard colours


- □ Platforms: Grey RAL 7016
- ☐ Free-wheel device: Base plate: Grey RAL 7016, Arms and slider: Red RAL 3020
- □ Ramps: Red RAL 3020



Technical data	
Lifting capacity	5,500 kg
Lifting height	1,895 mm
Working height	P: 2,060 mm WF: 2.210 - 2.270 mm
Cylinder diameter	8 x 140 mm
Distance between cylinders	1,240 - 1,850 mm
Lifting / lowering time	app. 38 Sec.
Foundation depth	2,625 mm
Pump unit	3.0 kW
Ecological hydraulic fluid	18
Voltage	230/400 V - 50 Hz - 16 A

Arm superstructure	
Total width	3,265 mm
Lifting pad included in the delivery	11028 (135 - 195 mm)
Min. height	135 - 195 mm
Arm length, min max.	715 - 1,410 mm

Platforms	
Total length	app. 6,800 mm
Usable length of platform	5,500 mm
Wheel base	app. 5,000 mm
Platform width	650 mm
Distance between platforms	900 mm
Drive-on height	165 mm



autop Maschinenbau GmbH Sandkampstraße 90

48432 Rheine I Germany +49 5971 8602-02

**♣** +49 5971 8602-25

⊠ info@autopstenhoj.com

STENHOJ A/S

Barrit Langgade 188-190 7150 Barrit | Denmark

**4** +45 76821-330

**₽** +45 76821-331

info@autopstenhoj.com

info@autopstenhoj.c

# Versions:

### Steel cassette:

- ☐ Zinc-coated
- □ Coated

## Installation:

- ☐ Superstructure on floor
- ☐ Superstructure in floor with or without flush floor device

# Optional extras:

- □ LED-Lighting set□ Large program of extra pads

Special colours available on request!

